

OPEN COUNTRY® A/T III

ON-/OFF-ROAD ALL-TERRAIN TIRE

The Open Country A/T III is a revolutionary new all-terrain tire that delivers gripping off-road traction with responsive and predictable on-road handling. With a strong focus on wet performance, durability and treadwear life, and using Toyo's proprietary T-mode tire development and modeling technologies, Toyo introduces advances in tread design, construction and all-new compounding. The Open Country A/T III provides a quiet ride with exceptional stability, instilling driving confidence no matter the terrain. The Open Country A/T III is built to be tough and offers peace of mind and the durability to safely get there and get back home, regardless of terrain or weather. And with a treadwear warranty of up to 65,000 miles, outdoor adventurers can rely on the Open Country A/T III for the long haul.

MILEAGE WARRANTY

P-/Euro-Metric Sizes: 65,000 miles
LT-Sizes: 50,000 miles

UTQG

P-/Euro-Metric sizes:
- S-/T-rated 600 A B.
- H-rated 600 A A.

NEW TREAD COMPOUND AND DESIGN

- Provides confident wet braking and handling.
- Provides cut-and-chip resistance.
- Provides excellent off-road grip.
- Delivers a quiet and comfortable ride.

MORE EVENLY DISTRIBUTED VOID AREA

- Enhances on and off-road traction.
- Increases tread block rigidity for excellent handling stability.
- Provides better worn appearance.

STAGGERED SHOULDER LUGS

- Enhance off-road traction with biting edges.

INCREASED LATERAL GROOVES

- Enhance traction on all surfaces, including snow.

3D MULTI-WAVE SIPES

- Enhance wet and snow traction.
- Reduce irregular wear.

STONE-EJECTING BLOCKS

- Eject stones from grooves.

POPULAR FITMENTS

Chevrolet & GMC Trucks, SUVs and CUVs, Ford F-Series, CUVs and SUVs, Jeep, Ram Series, Toyota Trucks, SUVs and CUVs, Nissan Trucks, SUVs and CUVs



Three-Peak Mountain Snowflake qualified for severe snow conditions.



LT / SUV / CUV / COM VAN

LT

For the latest tire information,
please visit toyotires.com.

TOYO TIRES®

OPEN COUNTRY® A/T III

LT

LT / SUV / CUV / COM VAN

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE
15	P215/75R15	100T	SL	OWL	356060	5.5-(6.0)-7.0	28	12.7	27.7	8.5	1742	-	44	751
	P225/75R15	102T	SL	BSW	356070	(6.0)-7.5	29	12.9	28.3	8.8	1874	-	44	734
	P235/75R15	108T	XL	OWL	356080	6.0-(6.5)-8.0	32	13.0	28.9	9.3	2183	-	50	720
	LT235/75R15	104/101S	C	OWL	355610	6.0-(6.5)-8.0	37	16.0	29.1	9.3	1985	1820	50	714
	P265/75R15	112S	SL	OWL	355280	7.0-(7.5)-9.0	38	13.4	30.7	10.5	2469	-	44	677
	30X9.50R15LT	104S	C	OWL	356050	6.0-(7.5)-8.0	40	15.6	29.8	9.4	1985	-	50	698
	31X10.50R15LT	109S	C	OWL	355910	7.0-(8.5)-9.0	43	15.6	30.7	10.6	2270	-	50	676
16	215/65R16	102T	XL	BSW	356380	6.0-(6.5)-7.5	28	12.7	27.0	8.7	1874	-	50	769
	215/70R16	100T	SL	BSW	356090	5.5-(6.5)-7.0	29	12.7	27.9	8.7	1764	-	44	745
	LT215/85R16	115/112Q	E	BSW	355760	5.5-(6.0)-7.0	40	15.7	30.4	8.5	2680	2470	80	683
	225/70R16	103T	SL	OWL	356100	6.0-(6.5)-7.5	30	12.9	28.4	9.0	1929	-	44	731
	P225/75R16	104S	SL	BSW	355260	(6.0)-7.5	30	12.9	29.3	8.8	1984	-	44	709
	LT225/75R16	115/112Q	E	BSW	355600	(6.0)-7.5	38	15.9	29.3	8.8	2680	2470	80	709
	235/70R16	106T	SL	BSW	356110	6.0-(7.0)-8.0	32	13.0	29.0	9.4	2094	-	44	717
	235/70R16	106T	SL	OWL	356120	6.0-(7.0)-8.0	32	13.0	29.0	9.4	2094	-	44	717
	LT235/85R16	120/116R	E	BSW	355770	6.0-(6.5)-7.5	44	16.0	31.7	9.3	3042	2778	80	655
	P245/70R16	106S	SL	OWL	355210	6.5-(7.0)-8.0	35	13.1	29.5	9.8	2094	-	44	704
	P245/70R16	106S	SL	BSW	355220	6.5-(7.0)-8.0	34	13.1	29.5	9.8	2094	-	44	704
	LT245/75R16	120/116S	E	BSW	355620	6.5-(7.0)-8.0	44	16.1	30.5	9.8	3042	2778	80	682
	LT245/75R16	120/116S	E	OWL	355630	6.5-(7.0)-8.0	44	16.1	30.7	9.8	3042	2778	80	676
	245/75R16	111T	SL	OWL	356140	6.5-(7.0)-8.0	35	13.1	30.5	9.8	2403	-	44	682
	245/75R16	111T	SL	BSW	356130	6.5-(7.0)-8.0	36	13.1	30.5	9.8	2403	-	44	682
	255/65R16	109T	SL	BSW	356150	7.0-(7.5)-9.0	33	13.2	29.1	10.2	2271	-	44	715
	255/70R16	115T	XL	BSW	356160	6.5-(7.5)-8.5	38	13.2	30.1	10.2	2679	-	50	691
	255/70R16	115T	XL	OWL	356170	6.5-(7.5)-8.5	37	13.2	30.1	10.2	2679	-	50	691
	P265/70R16	111T	SL	OWL	355230	7.0-(8.0)-9.0	39	13.4	30.6	10.7	2403	-	44	678
	P265/70R16	111T	SL	BSW	355240	7.0-(8.0)-9.0	40	13.4	30.6	10.7	2403	-	44	678
	LT265/75R16	123/120R	E	BSW	355650	7.0-(7.5)-9.0	50	16.3	31.7	10.5	3415	3085	80	656
	LT265/75R16	123/120R	E	OWL	355660	7.0-(7.5)-9.0	48	16.3	31.9	10.5	3415	3085	80	651
	265/75R16	116T	SL	BSW	356180	7.0-(7.5)-9.0	41	13.4	31.7	10.5	2756	-	44	656
265/75R16	116T	SL	OWL	356190	7.0-(7.5)-9.0	41	13.4	31.7	10.5	2756	-	44	656	
LT285/75R16	126/123R	E	OWL	355670	7.5-(8.0)-9.5	55	16.5	33.1	11.3	3750	3415	80	628	
LT285/75R16	126/123R	E	BSW	355680	7.5-(8.0)-9.5	59	16.5	32.8	11.3	3750	3415	80	633	
LT295/75R16	128/125R	E	BSW	355720	7.5-(8.0)-10.0	62	16.6	33.4	11.6	3970	3640	80	622	
LT305/70R16	124/121R	E	BSW	355570	8.0-(9.0)-10.0	63	16.8	32.8	12.2	3525	3195	65	633	
LT315/75R16	127/124R	E	BSW	355730	8.0-(8.5)-10.5	66	16.9	34.6	12.3	3860	3525	65	601	
17	215/65R17	103T	XL	BSW	355890	6.0-(6.5)-7.5	29	12.7	28.0	8.7	1929	-	44	741
	225/60R17	103T	XL	BSW	356390	6.0-(6.5)-8.0	29	12.9	27.6	9.0	1929	-	50	752
	225/65R17	102T	SL	BSW	356400	6.0-(6.5)-8.0	31	12.9	28.5	9.0	1874	-	44	729
	235/65R17	108H	XL	BSW	356200	6.5-(7.0)-8.5	34	13.0	29.1	9.4	2205	-	50	715
	P235/75R17	108S	SL	BSW	355270	6.0-(6.5)-8.0	36	13.0	30.9	9.3	2205	-	44	673
	LT235/80R17	120/117R	E	BSW	355740	6.0-(6.5)-8.0	46	16.0	31.8	9.3	3085	2835	80	653
	245/65R17	111T	XL	BSW	356210	(7.0)-8.5	36	13.1	29.5	9.8	2403	-	50	704
	245/65R17	111T	XL	OWL	356220	(7.0)-8.5	34	13.1	29.5	9.8	2403	-	50	704
	LT245/70R17	119/116R	E	BSW	355470	6.5-(7.0)-8.0	44	16.1	30.6	9.8	3000	2755	80	680
	245/70R17	110T	SL	BSW	356230	6.5-(7.0)-8.0	37	13.1	30.6	9.8	2337	-	44	680
	LT245/75R17	121/118S	E	BSW	355640	6.5-(7.0)-8.0	47	16.1	31.5	9.8	3195	2910	80	660

Speed rated "0" = 99mph, "R" = 106mph, "S" = 112mph, "T" = 118mph, "H" = 130mph. "SL" = Standard Load, "XL" = Extra Load, "C" = 6-ply rating, "E" = 10-ply rating, "F" = 12-ply rating, "BSW" = Black Sidewall, "OWL" = Outline White Lettering. Bold designates measuring rim width. *Inflated dimensions.

SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE	
17	255/70R17	112T	SL	BSW	356240	6.5-(7.5)-8.5	38	13.2	31.1	10.2	2469	-	44	668	
	LT255/80R17	121/118R	E	BSW	355750	6.5-(7.0)-8.5	53	16.3	33.1	10.0	3195	2910	80	628	
	265/65R17	116T	XL	BSW	356250	7.5-(8.0)-9.5	39	13.4	30.6	10.7	2756	-	50	680	
	LT265/70R17	121/118S	E	BSW	355480	7.0-(8.0)-9.0	48	16.3	31.7	10.7	3195	2910	80	656	
	LT265/70R17	121/118S	E	OWL	355490	7.0-(8.0)-9.0	48	16.3	31.7	10.7	3195	2910	80	656	
	LT275/70R17	124/121T	E	BSW	356550	7.0-(8.0)-9.0	51	16.4	32.2	11.0	3525	3195	80	645	
	265/70R17	115T	SL	BSW	356260	7.0-(8.0)-9.0	41	13.4	31.7	10.7	2679	-	44	656	
	265/70R17	115T	SL	OWL	356270	7.0-(8.0)-9.0	42	13.4	31.7	10.7	2679	-	44	656	
	P285/70R17	117T	SL	BSW	355250	7.5-(8.5)-9.5	46	13.6	32.8	11.5	2833	-	44	634	
	LT285/70R17	116/113Q	C	BSW	355530	7.5-(8.5)-9.5	56	16.5	32.8	11.5	2755	2535	50	634	
	LT285/70R17	121/118S	E	OWL	355540	7.5-(8.5)-9.5	53	16.5	33.0	11.5	3195	2910	80	630	
	LT285/70R17	121/118S	E	BSW	355550	7.5-(8.5)-9.5	56	16.5	32.8	11.5	3195	2910	80	634	
	LT285/75R17	121/118S	E	BSW	355700	7.5-(8.0)-9.5	60	16.5	33.9	11.3	3195	2910	80	614	
	LT285/75R17	117/114Q	C	BSW	355690	7.5-(8.0)-9.5	59	16.5	33.9	11.3	2835	2600	50	614	
	LT305/70R17	121/118R	E	BSW	355580	8.0-(9.0)-10.0	65	16.8	33.9	12.2	3195	2910	65	614	
	LT315/70R17	113/110S	C	BSW	355590	8.0-(9.5)-10.5	67	16.9	34.4	12.7	2535	2335	35	604	
	35X11.50R17LT	118Q	C	BSW	355920	7.5-(9.0)-10.0	63	16.9	34.5	11.4	2910	-	50	602	
	35X12.50R17LT	121R	E	BSW	355960	8.0-(10.0)-10.5	70	16.9	34.5	12.5	3195	-	65	602	
	18	225/55R18	102H	XL	BSW	355830	6.0-(7.0)-8.0	30	12.9	27.8	9.2	1874	-	50	748
		225/60R18	104T	XL	BSW	356410	6.0-(6.5)-8.0	32	12.9	28.6	9.0	1984	-	50	726
235/60R18		107T	XL	BSW	355860	6.5-(7.0)-8.5	33	13.0	29.1	9.4	2149	-	50	714	
235/65R18		110T	XL	BSW	355900	6.5-(7.0)-8.5	36	13.0	30.0	9.4	2337	-	50	692	
245/60R18		109T	XL	BSW	355870	(7.0)-8.5	35	13.1	29.6	9.8	2271	-	50	703	
255/55R18		109H	XL	BSW	355840	7.0-(8.0)-9.0	36	13.2	29.0	10.4	2271	-	50	716	
255/70R18		113T	SL	BSW	356280	6.5-(7.5)-8.5	40	13.2	32.1	10.2	2535	-	44	647	
265/60R18		110T	SL	BSW	356290	7.5-(8.0)-9.5	39	13.4	30.5	10.7	2337	-	44	681	
265/65R18		114T	SL	BSW	356300	7.5-(8.0)-9.5	41	13.4	31.5	10.7	2601	-	44	659	
LT265/70R18		124/121Q	E	BSW	355500	7.0-(8.0)-9.0	48	16.3	32.6	10.7	3525	3195	80	636	
265/70R18		116T	SL	BSW	356310	7.0-(8.0)-9.0	44	13.4	32.6	10.7	2756	-	44	636	
LT275/65R18		113/110T	C	OWL	355380	(8.0)-9.5	51	16.4	32.3	11.0	2535	2335	50	643	
LT275/65R18		123/120S	E	BSW	355400	(8.0)-9.5	51	16.4	32.1	11.0	3415	3085	80	647	
LT275/65R18		123/120S	E	OWL	355410	(8.0)-9.5	51	16.4	32.3	11.0	3415	3085	80	643	
LT275/65R18		113/110T	C	BSW	355390	(8.0)-9.5	52	16.4	32.1	11.0	2535	2335	50	647	
275/65R18		116T	SL	BSW	356320	7.5-(8.0)-9.5	43	13.5	32.1	11.0	2756	-	44	647	
LT275/70R18		125/122S	E	OWL	355520	7.0-(8.0)-9.0	52	16.4	33.4	11.0	3640	3305	80	622	
LT275/70R18		125/122S	E	BSW	355510	7.0-(8.0)-9.0	50	16.4	33.2	11.0	3640	3305	80	626	
285/60R18		120S	XL	BSW	355880	8.0-(8.5)-10.0	46	13.6	31.5	11.5	3086	-	50	660	
LT285/65R18		125/122S	E	BSW	355430	(8.5)-10.0	55	16.5	32.6	11.5	3640	3305	80	638	
LT285/75R18		129/126S	E	BSW	355710	7.5-(8.0)-9.5	68	16.5	34.8	11.3	4080	3750	80	596	
LT295/70R18		129/126S	E	BSW	355560	7.5-(8.5)-10.0	62	16.6	34.3	11.8	4080	3750	80	606	
LT305/65R18		128/125Q	F	BSW	355450	(9.0)-11.0	66	16.8	33.6	12.2	3970	3640	80	619	
LT325/60R18		124/121S	E	BSW	355360	(9.5)-11.5	66	17.0	33.3	13.0	3525	3195	65	623	
LT325/65R18		127/124R	E	BSW	355460	(9.5)-11.5	71	17.0	34.6	13.0	3860	3525	65	600	
33X12.50R18LT		122Q	F	BSW	355930	8.5-(10.0)-11.0	65	16.9	32.5	12.5	3305	-	80	639	
35X12.50R18LT		128Q	F	BSW	355970	8.5-(10.0)-11.0	75	16.9	34.5	12.5	3970	-	80	602	
35X12.50R18LT		118R	D	BSW	356330	8.5-(10.0)-11.0	75	16.9	34.5	12.5	2910	-	50	602	
37X12.50R18LT		128Q	E	BSW	356010	8.0-(10.0)-10.5	71	16.9	36.5	12.5	3970	-	65	569	

LT / SUV / CUV / COM VAN

LT

OPEN COUNTRY® A/T III

LT

LT / SUV / CUV / COM VAN

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED P.W.M. WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE
19	255/55R19	111H	XL	BSW	356420	7.0-(8.0)-9.0	40	13.2	30.0	10.4	2403	-	50	692
	255/60R19	113H	XL	BSW	356450	7.0-(7.5)-9.0	41	13.2	31.1	10.2	2535	-	50	669
20	245/50R20	105H	XL	BSW	355790	7.0-(7.5)-8.5	37	13.1	29.7	10.0	2039	-	50	700
	P245/60R20	107T	SL	BSW	355200	(7.0)-8.5	38	13.1	31.6	9.8	2149	-	44	658
	255/50R20	109T	XL	BSW	355800	7.0-(8.0)-9.0	39	13.2	30.1	10.4	2271	-	50	691
	255/55R20	110H	XL	BSW	356430	7.0-(8.0)-9.0	40	13.2	31.0	10.4	2337	-	50	670
	265/50R20	111T	XL	BSW	355810	7.5-(8.5)-9.5	42	13.4	30.5	10.9	2403	-	50	682
	LT265/60R20	121/118S	E	BSW	355330	(8.0)-9.5	54	16.3	32.5	10.7	3195	2910	80	639
	275/55R20	117T	XL	BSW	355850	7.5-(8.5)-9.5	43	13.5	31.9	11.2	2833	-	50	651
	275/60R20	115T	SL	BSW	356340	7.5-(8.0)-9.5	45	13.5	33.0	11.0	2679	-	44	630
	LT275/60R20	123/120T	E	BSW	356510	(8.0)-9.5	55	16.4	33.0	11.0	3415	3085	80	630
	LT275/65R20	126/123S	E	BSW	355420	(8.0)-9.5	54	16.4	34.1	11.0	3750	3415	80	609
	P285/55R20	114T	SL	BSW	356440	8.0-(9.0)-10.0	45	13.6	32.4	11.7	2601	-	44	642
	LT285/55R20	122/119T	E	BSW	356350	8.5-(9.0)-10.0	54	16.5	32.4	11.7	3305	3000	80	642
	LT285/60R20	125/122R	E	BSW	355340	(8.5)-10.0	61	16.5	33.5	11.5	3640	3305	80	621
	LT295/55R20	123/120T	E	BSW	356360	8.5-(9.5)-10.5	58	16.6	32.8	12.2	3415	3085	80	634
	LT295/60R20	126/123S	E	BSW	355350	(8.5)-10.5	60	16.6	33.9	11.8	3750	3415	80	612
	LT295/65R20	129/126S	E	BSW	355440	(8.5)-10.5	62	16.6	35.1	11.8	4080	3750	80	592
	305/50R20	120T	XL	BSW	355820	8.5-(9.5)-11.0	50	13.9	32.0	12.4	3086	-	50	648
	LT305/55R20	125/122Q	F	BSW	355320	9.0-(9.5)-11.0	66	16.8	33.2	12.4	3640	3305	80	625
	LT325/60R20	126/123R	E	BSW	355370	(9.5)-11.5	63	17.0	35.4	13.0	3750	3415	65	588
	35X11.50R20LT	124R	E	BSW	356480	8.0-(9.0)-10.5	66	16.9	34.5	11.4	3525	-	80	602
33X12.50R20LT	119Q	F	BSW	355940	8.5-(10.0)-11.0	76	16.9	32.5	12.5	3000	-	80	639	
35X12.50R20LT	121R	E	BSW	355980	8.5-(10.0)-11.0	72	16.9	34.5	12.5	3195	-	65	602	
35X12.50R20LT	125Q	F	BSW	355990	8.5-(10.0)-11.0	71	16.9	34.5	12.5	3640	-	80	602	
35X13.50R20LT	126Q	F	BSW	356040	9.5-(11.0)-12.0	71	16.9	34.5	13.6	3750	-	80	602	
37X12.50R20LT	126Q	E	BSW	356020	8.5-(10.0)-11.0	73	16.9	36.5	12.5	3750	-	65	569	
22	285/45R22	114H	XL	BSW	355780	9.0-(9.5)-10.5	45	13.6	32.1	11.2	2601	-	50	647
	LT285/50R22	121/118R	E	BSW	355290	8.5-(9.0)-10.0	56	16.5	33.3	11.7	3195	2910	80	624
	LT285/55R22	124/121S	E	BSW	355310	8.5-(9.0)-10.0	63	16.5	34.4	11.7	3525	3195	80	604
	LT295/50R22	122/119T	E	BSW	356490	8.5-(9.5)-10.5	62	16.6	33.7	12.2	3305	3000	80	617
	LT295/55R22	125/122T	E	BSW	356460	8.0-(9.5)-10.5	63	16.6	34.8	12.2	3640	-	80	598
	305/45R22	118S	SL	BSW	356370	9.5-(10.0)-11.5	48	13.9	32.8	11.90	2910	-	50	633
	LT325/50R22	127Q	F	BSW	355300	9.5-(10.0)-11.5	67	17.0	34.8	13.2	3860	-	80	596
	33X12.50R22LT	109R	E	BSW	355950	8.5-(10.0)-11.0	56	16.9	32.5	12.5	2270	-	65	639
	35X12.50R22LT	121Q	F	BSW	356000	8.5-(10.0)-11.0	64	16.9	34.5	12.5	3195	-	80	602
	37X12.50R22LT	127Q	F	BSW	356030	8.5-(10.0)-11.0	73	16.9	36.5	12.5	3860	-	80	569



OPEN COUNTRY A/T III
P/EURO-METRIC

OPEN COUNTRY A/T III
LT-METRIC

OPEN COUNTRY A/T III
FLotation

OPEN COUNTRY A/T III
OWL AVAILABLE