

## ON-/OFF-ROAD COMMERCIAL GRADE TIRE

The Open Country C/T boasts all-terrain commercial grade durability, plus a Three-Peak Mountain Snowflake qualifies it for severe snow conditions. Developed for balanced on- and off-road work, its unique tread design and tough construction deliver long tread life and traction in gravel, mud, and snow. Contrary to its aggressive appearance, the Open Country C/T also provides a quiet, comfortable highway ride.

LT

LIGHT TRUCK / SUV / CUV

### POPULAR FITMENTS

Chevrolet Silverado  
Ford F-Series  
Ram Series  
Toyota Tundra  
Nissan Titan



Three-Peak Mountain  
Snowflake qualified for  
severe snow conditions.

### HIGH TURN-UP, 3-PLY POLYESTER CONSTRUCTION

- Contributes to excellent durability, impact resistance, and handling.

### BALANCED TREAD COMPOUND

- Helps resist cutting, chipping, and stone drilling while remaining flexible in lower temperatures.
- Extends tire life and provides dependable year-round service.

### DUAL-ANGLE SHOULDER BLOCKS

- Enhances traction in snow, mud, and rutted road conditions.

### OPEN SHOULDER DESIGN

- Helps provide traction in mild mud, slush, and snow.

### PINNED FOR STUDS

- Able to accept TSMI #15 studs to aid in ice traction.



# SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)**	OVERALL WIDTH (IN.)**	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE
16	LT215/85R16	115/112Q	E	BSW	345220	5.5- <b>(6.0)</b> -7.0	46	17.0	30.4	8.5	2680	2470	80	683
	LT225/75R16	115/112Q	E	BSW	345180	<b>(6.0)</b> -7.0	45	17.0	29.3	8.8	2680	2470	80	709
	LT235/85R16	120/116Q	E	BSW	345160	6.0- <b>(6.5)</b> -7.5	55	18.3	31.7	9.3	3042	2778	80	655
	LT245/75R16	120/116Q	E	BSW	345050	6.5- <b>(7.0)</b> -8.0	51	18.3	30.7	9.8	3042	2778	80	676
	LT265/75R16	123/120Q	E	BSW	345170	7.0- <b>(7.5)</b> -8.0	57	18.4	31.7	10.5	3415	3085	80	656
	LT285/75R16	116/113Q	C	BSW	345190	7.5- <b>(8.0)</b> -9.0	62	18.4	32.8	11.3	2755	2535	50	633
17	LT225/75R17	116/113Q	E	BSW	345210	<b>(6.0)</b> -7.5	49	17.0	30.3	8.8	2755	2535	80	685
	LT235/80R17	120/117Q	E	BSW	345090	6.0- <b>(6.5)</b> -7.5	53	18.3	32.0	9.3	3085	2835	80	648
	LT245/70R17	119/116Q	E	BSW	345070	6.5- <b>(7.0)</b> -8.0	51	18.3	30.8	9.8	3000	2755	80	675
	LT265/75R17	121/118Q	E	BSW	345030	6.5- <b>(7.0)</b> -7.5	54	18.3	31.7	9.8	3195	2910	80	655
	LT265/70R17	121/118Q	E	BSW	345010	7.0- <b>(8.0)</b> -8.5	58	18.4	31.9	10.7	3195	2910	80	651
	LT285/70R17	121/118Q	E	BSW	345000	7.5- <b>(8.5)</b> -9.0	61	18.4	33.0	11.5	3195	2910	80	630
	35X12.50R17LT	121Q	E	BSW	345120	8.5- <b>(10.0)</b> -11.0	77	19.3	34.8	12.5	3195	-	65	598
18	LT265/70R18	124/121Q	E	BSW	345060	7.0- <b>(8.0)</b> -9.0	57	18.4	32.9	10.7	3525	3195	80	632
	LT275/65R18	123/120Q	E	BSW	345040	7.5- <b>(8.0)</b> -9.0	59	18.4	32.3	11.0	3415	3085	80	643
	LT275/70R18	125/122Q	E	BSW	345020	7.0- <b>(8.0)</b> -8.5	62	18.4	33.4	11.0	3640	3305	80	621
	LT295/70R18	129/126Q	E	BSW	345240	7.5- <b>(8.5)</b> -10.0	71	18.4	34.5	11.8	4080	3750	80	605
	35X12.50R18LT	123Q	E	BSW	345130	8.5- <b>(10.0)</b> -11.0	79	19.3	34.8	12.5	3415	-	65	598
20	LT265/60R20	121/118Q	E	BSW	345110	7.5- <b>(8.0)</b> -9.5	61	18.4	32.8	10.7	3195	2910	80	634
	LT275/55R20	115/112Q	D	BSW	345100	7.5- <b>(8.5)</b> -9.5	62	18.4	32.1	11.2	2680	2470	65	647
	LT275/65R20	126/123Q	E	BSW	345080	7.5- <b>(8.0)</b> -9.5	65	18.4	34.3	11.0	3750	3415	80	605
	LT285/55R20	122/119Q	E	BSW	345150	8.0- <b>(9.0)</b> -10.0	65	18.4	32.6	11.7	3305	3000	80	637
	LT285/60R20	125/122Q	E	BSW	345200	8.0- <b>(8.5)</b> -10.0	64	18.4	33.5	11.5	3640	3305	80	621
	LT295/65R20	129/126Q	E	BSW	345230	8.0- <b>(8.5)</b> -10.0	78	18.4	35.4	11.8	4080	3750	80	588
	35X12.50R20LT	121Q	E	BSW	345140	8.5- <b>(10.0)</b> -11.0	73	19.3	34.8	12.5	3195	-	65	598

LIGHT TRUCK / SUV / CUV

LT



Speed rated "Q" = 99 mph, "D" = 8-ply rating, "E" = 10-ply rating, "BSW" = Black Sidewall. Bold designates measuring rim width. \*\*Inflated dimensions.

For the latest tire information, please visit [toyotires.com](http://toyotires.com). **TOYO TIRES®**