

#### FOUR WIDE CIRCUMFERENTIAL GROOVES

- Evacuates water to improve wet traction.

# OPEN COUNTRY Q/T

LIGHT TRUCK / SUV / CUV

LT

#### OPEN LATERAL SLITS

- Improves water drainage for better wet performance.

#### SILENT WALL™ TECHNOLOGY

- Provides a quieter ride by reducing pipe resonance.

#### MULTI-WAVE SIPES

- Minimizes irregular wear for a smooth, quiet ride.
- Improves braking on wet and dry roads.
- Improves light snow traction.



\*See [toyotires.com](http://toyotires.com) for details.

For the latest tire information, please visit [toyotires.com](http://toyotires.com). **TOYO TIRES®**

# OPEN COUNTRY® Q/T

LT

LIGHT TRUCK / SUV / CUV

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)*	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE
16	215/70R16	100H	SL	BSW	318050	5.5- <b>(6.5)</b> -7.0	29	12.2	27.9	8.7	1764	-	51	745
	225/70R16	103H	SL	BSW	318060	6.0- <b>(6.5)</b> -7.5	31	12.3	28.4	9.0	1929	-	51	731
	P235/70R16	104T	SL	BSW	318070	6.0- <b>(7.0)</b> -8.0	33	12.5	29.0	9.4	1984	-	44	717
	255/65R16	109H	SL	BSW	318120	7.0- <b>(7.5)</b> -9.0	37	12.7	29.1	10.2	2271	-	51	715
17	225/65R17	102H	SL	BSW	318010	6.0- <b>(6.5)</b> -8.0	31	12.3	28.5	9.0	1874	-	51	729
	235/60R17	102T	SL	BSW	318160	6.5- <b>(7.0)</b> -8.5	33	12.5	28.1	9.4	1874	-	44	739
	235/65R17	108V	XL	BSW	318090	6.5- <b>(7.0)</b> -8.5	33	12.0	29.1	9.4	2205	-	50	715
	P245/65R17	105H	SL	BSW	318110	<b>(7.0)</b> -8.5	37	12.6	29.5	9.8	2039	-	51	704
	255/60R17	106V	SL	BSW	318190	7.0- <b>(7.5)</b> -9.0	36	12.2	29.1	10.2	2094	-	51	715
	P265/65R17	110S	SL	BSW	318140	7.5- <b>(8.0)</b> -9.5	42	12.9	30.6	10.7	2337	-	44	680
	P265/70R17	113H	SL	BSW	318000	7.0- <b>(8.0)</b> -9.0	42	12.9	31.7	10.7	2535	-	51	656
	235/55R18	100V	SL	BSW	318240	6.5- <b>(7.5)</b> -8.5	32	12.0	28.1	9.6	1764	-	51	738
18	235/60R18	107V	XL	BSW	318170	6.5- <b>(7.0)</b> -8.5	33	12.0	29.1	9.4	2149	-	50	714
	235/65R18	106V	SL	BSW	318390	6.5- <b>(7.0)</b> -8.5	35	11.7	30.0	9.4	2094	-	51	692
	245/60R18	105H	SL	BSW	318180	<b>(7.0)</b> -8.5	35	12.6	29.6	9.8	2039	-	51	703
	255/55R18	109V	XL	BSW	318020	7.0- <b>(8.0)</b> -9.0	36	12.2	29.0	10.4	2271	-	50	716
	255/60R18	112V	XL	BSW	318200	7.0- <b>(7.5)</b> -9.0	37	12.2	30.0	10.2	2469	-	50	692
	P255/65R18	109S	SL	BSW	318130	7.0- <b>(7.5)</b> -9.0	39	12.7	31.1	10.2	2271	-	44	669
	265/60R18	110V	SL	BSW	318220	7.5- <b>(8.0)</b> -9.5	40	12.2	30.5	10.7	2337	-	51	681
	P265/65R18	112H	SL	BSW	318150	7.5- <b>(8.0)</b> -9.5	43	12.9	31.5	10.7	2469	-	51	659
19	P225/55R19	99V	SL	BSW	318230	6.0- <b>(7.0)</b> -8.0	33	11.8	28.8	9.2	1709	-	51	722
	235/50R19	99V	SL	BSW	318380	6.5- <b>(7.5)</b> -8.5	32	11.7	28.3	9.6	1709	-	51	734
	235/55R19	105V	XL	BSW	318250	6.5- <b>(7.5)</b> -8.5	33	12.0	29.2	9.6	2039	-	50	712
	P245/55R19	103H	SL	BSW	318270	7.0- <b>(7.5)</b> -8.5	36	12.6	29.6	10.0	1929	-	51	701
	255/50R19	107V	XL	BSW	318330	7.0- <b>(8.0)</b> -9.0	36	12.2	29.1	10.4	2149	-	50	714
	255/55R19	111V	XL	BSW	318280	7.0- <b>(8.0)</b> -9.0	38	12.2	30.0	10.4	2403	-	50	692
	255/60R19	109H	SL	BSW	318210	7.0- <b>(7.5)</b> -9.0	40	12.7	31.1	10.2	2271	-	51	669
	265/50R19	110V	XL	BSW	318350	7.5- <b>(8.5)</b> -9.5	38	12.2	29.5	10.9	2337	-	50	704
20	275/55R19	111V	SL	BSW	318300	7.5- <b>(8.5)</b> -9.5	42	12.3	30.9	11.2	2403	-	51	672
	235/55R20	102V	SL	BSW	318370	6.5- <b>(7.5)</b> -8.5	35	12.5	30.2	9.6	1874	-	51	689
	P245/50R20	102V	SL	BSW	318320	7.0- <b>(7.5)</b> -8.5	37	12.1	29.7	10.0	1874	-	51	700
	255/50R20	109V	XL	BSW	318340	7.0- <b>(8.0)</b> -9.0	36	12.2	30.1	10.4	2271	-	50	691
	255/55R20	110V	XL	BSW	318290	7.0- <b>(8.0)</b> -9.0	39	12.2	31.0	10.4	2337	-	50	670
	265/50R20	111V	XL	BSW	318360	7.5- <b>(8.5)</b> -9.5	39	12.2	30.5	10.9	2403	-	50	682
22	P285/45R22	110H	SL	BSW	318030	9.0- <b>(9.5)</b> -10.5	47	12.5	32.1	11.2	2337	-	51	647

Speed rated "S" = 112mph, "T" = 118mph, "H" = 130mph, "V" = 149mph. "SL" = Standard Load, "XL" = Extra Load, "BSW" = Black Sidewall. Bold designates measuring rim width. \*Inflated dimensions.