

## ON-/OFF-ROAD RUGGED TERRAIN TIRE

Off-road performance meets on-road comfort with the Open Country R/T. Built rugged for any terrain, this tire offers excellent off-road traction, durable construction, and aggressive styling. Its ability to tackle dirt, sand, and rocks is inspired by the legendary Open Country M/T, while its quieter ride is a nod to our best-selling Open Country A/T II.

LT

LIGHT TRUCK / SUV / CUV

### MILEAGE WARRANTY\*

45,000 miles

### POPULAR FITMENTS

Chevrolet Trucks  
Ford F-Series  
Jeep  
Nissan Trucks  
Ram Series  
Toyota Trucks



### HIGH TURN-UP, 3-PLY POLYESTER CONSTRUCTION

- Contributes to excellent durability, impact resistance, and handling.

### OPTIMIZED PATTERN ARRANGEMENT

- Reduces noise for improved driving comfort.

### AGGRESSIVE SIDEWALL DESIGNS WITH DURABLE SIDEWALL COMPOUND

- Enhances traction and side impact protection.
- Offers customization with a distinct look on each side of the tire.

### OPEN, SCALLOPED SHOULDER BLOCKS

- Improves off-road traction.
- Enhances grip in muddy, sandy, or snowy off-road conditions.
- Ejects mud and snow through the open channels.

### STONE AND MUD EJECTORS

- Forces stones and mud from grooves.



# OPEN COUNTRY® R/T

LT

LIGHT TRUCK / SUV / CUV

	WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)**	OVERALL WIDTH (IN.)**	MAX LOAD (LBS) SINGLE	MAX LOAD (LBS) DUAL	MAX PRESSURE (PSI)	REVS PER MILE
15		31X10.50R15LT	109Q	C	BSW	351360	7.0-( <b>8.5</b> )-9.0	57	19	30.5	10.6	2270	-	50	681
	16	LT265/75R16	123/120Q	E	BSW	350720	7.0-( <b>7.5</b> )-8.0	53	16	31.9	10.5	3415	3085	80	651
		LT285/75R16	126/123Q	E	BSW	351640	7.5-( <b>8.0</b> )-9.0	59	16	32.8	11.3	3750	3415	80	633
		LT305/70R16	124/121Q	E	BSW	351670	8.0-( <b>9.0</b> )-9.5	63	16	32.8	12.2	3525	3195	65	633
LT315/75R16		127/124Q	E	BSW	351650	8.0-( <b>8.5</b> )-11.0	67	16	34.6	12.3	3860	3525	65	601	
17	LT255/80R17	121/118Q	E	BSW	351630	6.5-( <b>7.0</b> )-8.5	56	16	33.1	10.0	3195	2910	80	628	
	LT265/70R17	121/118Q	E	BSW	353460	7.0-( <b>8.0</b> )-8.5	56	16	31.7	10.7	3195	2910	80	656	
	LT285/70R17	121/118Q	E	BSW	350160	7.5-( <b>8.5</b> )-9.0	60	16	33.0	11.5	3195	2910	80	630	
	LT285/75R17	121/118Q	E	BSW	353480	7.5-( <b>8.5</b> )-9.5	62	16	33.9	11.3	3195	2910	80	614	
	LT295/70R17	121/118Q	E	BSW	351210	7.5-( <b>8.5</b> )-10.0	64	16	33.3	11.8	3195	2910	80	624	
	LT305/70R17	121/118Q	E	BSW	353540	8.0-( <b>9.0</b> )-9.5	65	16	33.9	12.2	3195	2910	65	614	
	LT315/70R17	113/110S	C	BSW	353550	8.0-( <b>9.5</b> )-11.0	68	16	34.4	12.7	2535	2335	35	604	
	33X12.50R17LT	114Q	D	BSW	353570	8.5-( <b>10.0</b> )-11.0	67	19	32.8	12.5	2600	-	50	634	
	35X12.50R17LT	121Q	E	BSW	350210	8.5-( <b>10.0</b> )-11.0	74	19	34.8	12.5	3195	-	65	598	
	37X12.50R17LT	124Q	D	BSW	350700	8.5-( <b>10.0</b> )-11.0	78	19	36.8	12.5	3525	-	50	565	
37X13.50R17LT	121Q	D	BSW	350670	8.5-( <b>11.0</b> )	84	19	36.8	13.6	3195	-	50	565		
18	LT275/65R18	123/120Q	E	BSW	353470	7.5-( <b>8.0</b> )-9.0	58	16	32.1	11.0	3415	3085	80	647	
	LT275/70R18	125/122Q	E	BSW	351220	7.0-( <b>8.0</b> )-8.5	61	16	33.2	11.0	3640	3305	80	626	
	LT285/60R18	122/119Q	E	BSW	351280	8.0-( <b>8.5</b> )-10.0	58	16	31.5	11.5	3305	3000	80	660	
	LT285/65R18	125/122Q	E	BSW	350260	8.0-( <b>8.5</b> )-10.0	59	16	32.8	11.5	3640	3305	80	633	
	LT285/75R18	129/126Q	E	BSW	351250	7.5-( <b>8.0</b> )-9.5	66	16	34.8	11.3	4080	3750	80	596	
	LT295/70R18	129/126Q	E	BSW	353530	7.5-( <b>8.5</b> )-10.0	65	16	34.3	11.8	4080	3750	80	606	
	33X12.50R18LT	118Q	E	BSW	350220	8.5-( <b>10.0</b> )-11.0	65	19	32.8	12.5	2910	-	65	634	
	35X12.50R18LT	123Q	E	BSW	350170	8.5-( <b>10.0</b> )-11.0	77	19	34.8	12.5	3415	-	65	598	
	37X12.50R18LT	128Q	E	BSW	353590	8.5-( <b>10.0</b> )-10.5	79	19	36.8	12.5	3970	-	65	565	
	37X13.50R18LT	124Q	D	BSW	351270	8.5-( <b>11.0</b> )	85	19	36.8	13.6	3525	-	50	565	
20	LT275/65R20	126/123Q	E	BSW	351200	7.5-( <b>8.0</b> )-9.5	60	16	34.1	11.0	3750	3415	80	609	
	LT285/55R20	122/119Q	E	BSW	351240	8.0-( <b>9.0</b> )-10.0	60	16	32.4	11.7	3305	3000	80	642	
	LT285/60R20	125/122Q	E	BSW	351690	8.0-( <b>8.5</b> )-10.0	62	16	33.5	11.5	3640	3305	80	621	
	LT295/55R20	123/120Q	E	BSW	351620	8.0-( <b>9.5</b> )-10.0	64	16	32.8	12.2	3415	3085	80	634	
	LT295/60R20	126/123Q	E	BSW	353510	8.0-( <b>8.5</b> )-10.0	67	16	33.9	11.8	3750	3415	80	612	
	LT295/65R20	129/126Q	E	BSW	353520	8.0-( <b>8.5</b> )-10.0	69	16	35.1	11.8	4080	3750	80	592	
	LT305/55R20	125/122Q	F	BSW	351480	8.5-( <b>9.5</b> )-11.0	65	16	33.2	12.4	3640	3305	80	625	
	LT305/55R20	121/118Q	E	BSW	351230	8.5-( <b>9.5</b> )-11.0	67	16	33.2	12.4	3195	2919	65	625	
	LT315/60R20	125/122Q	E	BSW	351660	8.5-( <b>9.5</b> )-11.0	72	16	34.9	12.7	3640	3305	65	596	
	LT325/60R20	126/123Q	E	BSW	351680	9.0-( <b>9.5</b> )-12.0	75	16	35.4	13.0	3750	3415	65	588	
33X12.50R20LT	114Q	E	BSW	350180	8.5-( <b>10.0</b> )-11.0	69	19	32.8	12.5	2600	-	65	634		
35X11.50R20LT	124Q	E	BSW	353580	8.0-( <b>9.0</b> )-10.5	68	19	34.8	11.4	3525	-	80	598		
35X12.50R20LT	121Q	E	BSW	350190	8.5-( <b>10.0</b> )-11.0	75	19	34.8	12.5	3195	-	65	598		
35X12.50R20LT	125Q	F	BSW	351470	8.5-( <b>10.0</b> )-11.0	71	19	34.8	12.5	3640	-	80	598		
35X13.50R20LT	121Q	E	BSW	350690	9.5-( <b>11.0</b> )-12.0	76	19	34.8	13.6	3195	-	65	598		
37X12.50R20LT	126Q	E	BSW	350230	8.5-( <b>10.0</b> )-11.0	81	19	36.8	12.5	3750	-	65	565		
37X13.50R20LT	127Q	E	BSW	350680	8.5-( <b>11.0</b> )	82	19	36.8	13.6	3860	-	65	565		
38X13.50R20LT	128Q	E	BSW	353600	9.5-( <b>11.0</b> )-12.0	86	19	37.8	13.6	3970	-	65	550		

Speed rated "Q" = 99mph. "D" = 8-ply rating, "E" = 10-ply rating, "F" = 12-ply rating. "BSW" = Black Sidewall. Bold designates measuring rim width. \*\*Inflated dimensions.

# SPECIFICATIONS

WHEEL DIA.	TIRE SIZE	LOAD/SPEED	LOAD ID	SIDEWALL	PRODUCT CODE	APPROVED RIM WIDTH RANGE (IN.)	WEIGHT (LBS)	TREAD DEPTH (1/32")	OVERALL DIA. (IN.)*	OVERALL WIDTH (IN.)**	MAX. LOAD (LBS) SINGLE	MAX. LOAD (LBS) DUAL	MAX. PRESSURE (PSI)	REVS PER MILE
22	LT295/50R22	122/119Q	E	BSW	353490	8.0-( <b>9.5</b> )-10.5	74	16	33.7	12.2	3305	3000	80	617
	LT295/55R22	125/122Q	E	BSW	353500	8.0-( <b>9.5</b> )-10.5	67	16	34.8	12.2	3640	3305	80	598
	LT325/50R22	127Q	F	BSW	353560	9.0-( <b>10.0</b> )-12.0	78	16	34.8	13.2	3860	-	80	596
	35X12.50R22LT	117Q	E	BSW	350710	8.5-( <b>10.0</b> )-11.0	67	19	34.8	12.5	2835	-	65	598
	37X12.50R22LT	123Q	E	BSW	350730	9.0-( <b>10.0</b> )-11.5	77	19	36.8	12.5	3415	-	65	565
	37X13.50R22LT	123Q	E	BSW	351260	8.5-( <b>11.0</b> )	81	19	36.8	13.6	3415	-	65	565
	38X13.50R22LT	126Q	E	BSW	353610	9.5-( <b>11.0</b> )-12.0	88	19	37.8	13.6	3760	-	65	550
	38X15.50R22LT	128Q	E	BSW	353620	11.0-( <b>12.5</b> )-14.0	92	19	37.8	15.6	3970	-	65	550
24	37X13.50R24LT	124Q	F	BSW	353730	9.5-( <b>11.0</b> )-12.0	87	19	36.8	13.6	3525	-	80	565
	38X15.50R24LT	128Q	F	BSW	353740	11.0-( <b>12.5</b> )-14.0	100	19	37.8	15.6	3970	-	80	550

LIGHT TRUCK / SUV / CUV

LT